

## **TECNO LINE**

#### MODELS:

## Compact C/D Germ FAN

Variant with:

Air Quality Sensor
SMOKE sensor
For rooms with smoke
Inox BOX (Standard)
White BOX (Option)



Patent application n. PCT/IB2009/055827

# BIPOLAR IONIZATION FOR AIR TREATMENT & SANIFICATION WITH OZONE CONTROLLED

Model	C Germ FAN	D Germ FAN
Environment volume (m³)	Min 20 – Max *80	Min 30 – Max *120
Air flow (m³/h)	40	60
Ionization type	Bipolar with 1 unit 195 mm type <b>C</b>	Bipolar with 1 unit 195 mm type <b>D</b>
Ventilation	Axial—1 speed	Axial—1 speed
Noise Level dB (A)	~ 40	~ 35
Weight (Kg)	3,3 – 3,8 (inox)	3,6 – 4,1 (inox)
Ionizing control	Automatic with Air Quality sensor & Adjustable sensitivity	Automatic with Air Quality sensor & Adjustable sensitivity
Power consumption (W)	20	25
Dimension L/W/H (mm)	380/120/120	380/120/120
Supply voltage	230 V/ 1 /50 Hz	230 V/ 1 /50 Hz
Air filtration type	G4	G4
Remote control	With potentiometer	With potentiometer

\* The values shown are purely indicative and should always be adjusted according to actual situations of use.

### **INSTALLATION**

Fixing	On the wall at a height of 1.8 mt.
Maintenance	Axial fan cleaning once a year.*
	Ionization tube cleaning every 6 months.*
	G4 filter replacement every 6 months.*
	Air Quality sensor calibration check every 5 years.

\* The values shown are purely indicative and should always be adjusted according to actual situations of use. Tubes replacement is recommended after 10000 operating hours.







REV.20-04



## **TECNO LINE**

#### MODELS:

### Compact C/D Germ FAN

Variant with:

Air Quality SensorFor environments with the presence of odorsSMOKE sensorFor rooms with smokeInox BOX (Standard)White BOX (Option)



Patent application n. PCT/IB2009/055827

### **BENEFITS OF TECHNOLOGY**

The "**Bipolar Controlled Ionization**" system patented by Periso SA guarantees better air quality, purifying it from harmful microorganisms and contaminants.

Thanks to a natural system of beneficial ions emission, it is possible to promote the **healthiness of the environment**, physical comfort and to improve respiratory activity.

The system is controlled by a **sensor** that is very sensitive to volatile organic compounds and suspended particulates. This enable the activation of effective oxygen clusters and the decomposition of many complex odorous molecules into simpler elements.

In this way the **proliferation** of microorganisms and molds is eliminated, thanks to the damage to their cell membrane.

**Food preservation** can be guaranteed as well thanks to the natural sanification system, without alter the organoleptic characteristics of food.

### FIELDS OF APPLICATION

- Health service sector
- Hotel and Catering
- Beauty & Fitness
- Offices
- Air treatment sector







